nal and/or subsequent record used to evaluate the corner position

ription of evidence found, note discrepancies in the record, state method of establishing lost corners.

Description of monument and accessories set to perpetunte the corner position.
Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

Certification must be signed and scaled by Registered Land Surveyor in State of Montana.
Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

Corner 1/4 Corner Sec 32/5

26N T. 25N

\_\_\_R. \_\_<u>32W</u>\_\_\_P.M.M. \_

Sanders

County

RECORD 1982:

THE 1/4 SEC. COR. OF SECS. 5 AND 32, MONUMENTED WITH AN ALUMINUM POST, 2 1/2 INS. DIAM., FIRMLY SET, PROJECTING 8 INS. ABOVE THE GROUND, ESTABLISHED BY CARL R. MCMILLEN, MONTANA REGISTERED LAND SURVEYOR, NO. 4659S, AND ACCEPTED AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL COR., WITH ALUMINUM CAP MKD.

> T26N R32W <u>32</u>

THE COR. IS SITUATED IN THE ROTTED REMAINS OF THE INTERSECTION OF OLD FENCES EXTENDING N. AND W., AND AT THE INTERSECTION OF NEW FENCES EXTENDING N. AND W.

FOUND: 3 1/4" DIAMETER ALUMINUM CAP PER 1982 RECORD, FROM WHICH

A 20" LARCH W/OVERGROWN BLAZE AND SIGN BEARS N 23° E, 21.8 FT.

A 12" BIRCH W/OVERGROWN BLAZE AND SIGN BEARS S 43° E, 18.8 FT.


SEE CERTIFICATE OF SURVEY NO. 1276 FOR DIMENSIONS TO ADJACENT CORNERS.

T26N R32W

CRM 4659S

209891

SKETCH OF CORNER



CERTIFICATION William W. Weikel

certify the information shown herein is true and correct.

Signature Ground Party Chief

William W. We kel certify that this Corner Record correctly represents work performed by me or under by direction in compliance with the Recordation Act" (70.22-101, ct seq., M.D.A.)

A) Signature of Surveyor & Scal

8-93 \_Reg. No. \_ 473 LS WGM group

Office of Clerk and Recorder, County of Dan N all . This "corner record" was filed for record on the 10 wat 27, 1993 (28: 30 was noted on the cross-index plat and is assigned page No. book No.

County Official

T. 25N R. 32W PMM

5

Sec.

· - corner this sheet