22/23 CERTIFIED CORNER RECORDATION Corner T. 28 N. R. 3 W. P.M.M. Pondera County 1874 GLO. Survey by William T. McFarland and Edward B. Bonnell, Book 755 Page 15 "Set a granite stone 16X6X6 in. 12 in. in the ground for Cor. to Secs. 22, 23, 26 and 27, marked with 2 notches on the S. and E. edges, raised a mound of stone alongside" 1997 Remonumentation by S. R. Smith 1 find no evidence of the original monument or its accessories. Interview with landowner to the south indicates that the roads near this corner were not necessarily built on the section lines. At the position calculated by double proportion, I set on aluminum pipe 6.3 cm. diameter, 76.2 cm. long, 88 cm. in the ground, with 8.255 cm. diameter M.D.O.H. aluminum cap, marked as shown below, from which, A 1.7 m. long galvanized steel post with M.D.T. survey decal attached, bears West, 5.58 m. dist. A spike with a 3.175 cm. diameter yellow plastic cap marked "SMITH 4740S", set 30 cm. above ground on the southwest side of a 29 cm. diameter powerpole with reference sign, bears N. 61' W., 10.394 m. dist.

Bearings listed in remonumentation section were measured with a hand compass, declination 15 1/2' East.

Refer to the Certificate of Survey filed in conjunction with this corner recordation for ties to adjacent section controlling corners.

