## 45322

BODK

1PAGE 561

INSTRUCTIONS iginal and/or subsequent record used to evaluate the corner position.

2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

Description of evidence found, note discrepancies in the receive, state intervents of evidence found, note discrepancies in the receive, state intervents of evidence for corners.
Description of monument and accessories set to perpetuate the corner position.
Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
Fill in Cross Index & Section Diagram at bottom of sheet.

**CERTIFIED CORNER RECORDATION** 

Corner S <sup>1</sup> / <sub>4</sub> Cor Sec 5			P.M.M. Valley	County
40 00 Set a granite stone	12x9x7 ins 8 i	ns in the	ground bor 1 sec.	cor, marked

a granite stone  $\frac{1}{4}$  on North face, dug pits 18x18x12 ins E & W of (stone  $5\frac{1}{2}$  ft dist and raised a mound of earth  $1\frac{1}{2}$  ft high  $3\frac{1}{2}$  ft base alongside. (1891 survey)

## EVIDENCE FOUND:

A graded road had been constructed along the section line and no evidence of the original stone could be found. Set a  $\frac{1}{2}$ " x 24" steel re-bar 6" bury at the intersection of N-S midsection road of long standing honored as the boundary by the property owners for many years in the centerline of the E-W County road and single proportioned the corner from known corners.

