

NOK



iginal and/or subsequent record used to evaluate the corner position. z_{φ} Description of evidence found, note discrepancies in the record, state method of establishing lost or obujerated corners.

corners.
Description of monument and accessories set to perpetuate the corner position.
Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner <u>NE Cor Sec</u> 14

T. <u>29 N R. <u>39</u>E P.M.M. Valley</u>

__County

GLO RECORD

80.00 Set a sand stone 12 X 9 X 5 inches 8 inches in the ground for cor. to secs. 10, 11, 14, and 15, marked with 4 notches on S. and 2 notches on E edges. Dug pits 18 X 18 X 12 inches in each sec. $5\frac{1}{2}$ feet dish and raised a mound of earth 2 feet high $4\frac{1}{2}$ feet base alongside. Land, gently rolling table Soil, sandy and clay 2nd rate No timber

EVIDENCE FOUND

None due to road construction set a $\frac{1}{2}$ X 24" Re bar with cap at cor. point. Set $\frac{1}{2}$ " X 24" re bar at road intersection to the East for RM.



A	11 12 5 EM. 12 14 13	CERTIFICATION I, D. C. Beckman certify the information shown herein is true and correct. D. C. Beckman Signature Ground Party Chief I, D. C. Beckman certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.) <u>D. C. Beckman</u> Signature of Surveyor & Seal Date: <u>8-14-84</u> Reg. No. <u>889</u> ES
	SKETCH OF CORNER	Employer: Owner Beckman Engineering
Office of Clerk and Recorder, County ofVALLEY This "corner Sec. 14 Sec. 14		
record" was filed for record on <u>MAY 9,1986 at 2:15 P.M.</u>		
was noted on the cross-index plat and is assigned page No. <u>694</u> , in book No. <u>1 of CORNER RECORDS</u> <u>Mary Low Eide</u> By Butta Bretzke Dep. County Official		
FEE: DH Cross Index No. <u>J21</u> T. <u>29N</u> R. <u>39E</u> PMM Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors		

64953