CR#219

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position. 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

corners.

Description of monument and accessories set to perpetuate the corner position.

Distription of monament and accessories set to perpendic the conter position.
Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner East¹/₄ Section 17

T. <u>30 N.</u> R. <u>30 E.</u> P.M.M. <u>Phillips</u>

County

1. ORIGINAL RECORD: Unknown

SUBSEQUENT RECORD: Position shown on Certificate of Survey No.127-no description.

- 2. EVIDENCE FOUND: Found 30d nail driven thru a SS&G yellow plastic cap in top of a 10"x10" railroad tie fence corner post, top of post is leaning westery ± 1 foot relative to the base. Found stone marked "¼" lying loose on surface near the corner post. Anterio an
- 3. MONUMENTATION:

Set a 5/8"x 18" rebar with 2" aluminum cap marked as shown below 1.5' East of SS&G yellow plastic cap in top of fence post at the point of intersection of existing E-W and North fence lines @ the East base of the 10"x10" railroad tie fence corner post, painted and flagged, and established the following reference monuments:

A 6" Russian Olive tree, marked "BT ¼" bears S 62⁰ W, 36.37 feet from corner.

