- INSTRUCTIONS
- Original and/or subsequent record used to evaluate the corner position.
   Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated
- corners.

corners.
Description of monument and accessories set to perpetuate the corner position.
Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
Certification must be signed and sealed by Land Surveyor registered in the State of Montana. 6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

SW Sec. Cor. 20

## T. 31 N. R. 33 W. P.M.M.

Lincoln

\_County

Corner 1893 G.L.O. Original Record by Daniel P. Mumbrue: Set a post, 4 ft. long, 4 ins. square, 24 ins. in the Ι. ground for Cor. to Secs. 19, 20, 29, 30. and marked four bearing trees.

1965 B.L.M. Remonumentation Record by D. Lindenberg: "The cor. of secs. 19, 20, 29, 30, determined from the remains of the original bearing trees. At the corner point, set an iron post, 30 ins. long,  $2 \frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



from which

The original bearing trees:

- A stump, 24 ins. diam., bears N45  $1/4^{\circ}$ E, 70 lks. dist., no marks. (Record) A fir, 30 ins. diam., bears S75  $3/4^{\circ}$ E, 24 lks. dist., with overgrown blaze. (Record) A burnt stump, bears S 4  $1/2^{\circ}$ W, 42 lks. dist., no marks. (Record) A larch, 25 ins. diam., bears N32  $1/2^{\circ}$ W, 39 lks. dist., with an overgrown blaze. (Record)

The new bearing trees:

A fir, 11 ins. diam., bears N32  $1/2^{\circ}$ E, 37 lks. dist., mkd. T31N R33W S20 BT. A larch, 21 ins. diam., bears S79  $1/2^{\circ}$ W, 12 lks. dist., mkd. T31N R33W S30 BT."

- II. Found a 2 1/2 in. diam. iron pipe, 2 ins. above ground, with a 3 1/4 in. diam. brass cap marked as shown above, from which:
  - A fir, 13 ins. diam., bears  $N35^{\circ}E$ , 24.4 ft. dist., overgrown scribe. (BLM) A stump, 20 ins., diam., bears  $N45^{\circ}E$ , 46.4 ft. dist., no scribing visible. (Original) A fir, 34 ins. diam., bears S77°E, 15.8 ft. dist., overgrown scribe. (Original) A larch, 24 ins. diam., S82°W, 8.0 ft. dist., overgrown scribe. (BLM) A root crown, 18 ins. diam., bears S06°W, 27.3 ft. dist., no sribing visible. (Original)

III. Painted red bands around the bearing trees and attached Land Survey Monument and Bearing Tree signs. Set a 6 ft. galvanized steel guard post with Land Survey Marker and Property Boundary decals, East, 3.0 ft.

R 20" 5TUMP	CERTIFICATION
A 13"FIR	Gary Crismon
	certify the information shown herein is true and correct.
13"FIR N35°E N45°E 24,4 FT. 46,4 FT.	Harry C. Crismon Signature Ground Party Chief, 1999
ATIT FUL TOUT FU	Signature Ground Party Chief
	Alvah F. Hughes ANTAA
N 24" LARCH 8.0 FT. 15.8 FT. 7 34" FIR	certify that this Corner Record correctly represents work performed.
N - 24" LARGH 8.0 FT. 15.8 FT. 734" FIR	by me or under my direction in compliance with the Comen
N 24" LARCH SIN. A 34" FIR	Recordation Act" (70-22-101, et seqM.CA.) A LVAH F.
× 40	alwah t. placethe HES
	Signature of Surveyor & Soal 3 2 2 L S
	Date:Reg. No7322 PS
D 18" ROOT CROWN	
SKETCH OF CORNER	Employer: U.S. FOREST SERVICE
	Soo in the second
and a standard the standard	This "corner Sec. 20
Office of Clerk and Recorder, County of	This corner
record" was filed for record on Dec 3, 1990	
was noted on the cross-index plat and is assigned page No. $4$	3.34 in $+-+1$
was noted on the cross-index plat and is assigned page No.	, , , , , , , , , , , , , , , , , , , ,
the set of heart	he Bull Brack
book No.	
County Offi	Clai
R-05	31 N 33 W
Cross Index No	T R PMM • - corner this sheet

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors