## INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.

2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners

corners.

3. Description of monument and accessories set to perpetuate the corner position.

4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

1/4 20/29 Corner

31N

R. 33W

\_\_P.M.M. Lincoln

Record 1965 BLM Remonumentation.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with bronze cap marked (see diagram below) from which: Original bearing trees:

Stump, 22" diam., bears S 72°E 12 Lks. (7.9'), mkd. 1/4 S B.T. (Record)

Stump, 12" diam., bears N 58 3/4 W 42 Lks. (27.7'), 4 S. B.T. (Record)

New bearing trees: A larch, 7" diam., bears S 40°E 55 Lks. (36.3'), mkd. 1/4 S 29 B.T. A larch, 9" diam., bears N 49°W 23 Lks. (15.2'), mkd. 1/4 S 20 B.T.

Record 1977. Surveyor Marquardt 2989 ES found BLM brass cap and new bearing trees. He also located two additional reference monuments as follows: A 10" fir bears N  $22^\circ$  E to center of tree and 14.02 feet to a spike in the side of tree. A 12" tamarack bears S  $55^{\circ}\text{E}$  to center of tree and 41.70 feet to spike in side of tree.

Found 1989. BLM brass cap, marked as per diagram below, 8" above ground with evidence of all bearing trees substantially as described in the record.

No new references established.

See Certificate of Survey Number 1734 for ties to other corners.

