INSTRUCTIONS 1. Original and/or subsequent record used to evaluate the corner position. 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners. 3. Description of monument and accessories set to perpetuate the corner position. 4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc. 5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana. 6. Fill in Cross Index & Section Diagram at bottom of sheet.							
forr E. 6 A f: A Ta T311 A Ta T311 A Ta T311 A Ta T311 2. After con 3. Set: A C A 1	chains: Set a sand her of sections 13, edges;from which ir, 28 inches diame amarack, 16 inches NR34WS24B.T. amarack, 26 inches NR34WS23B.T. amarack, 28 inches NR34WS14B.T. diligent search it struction of Callah A 3" X 30" aluminum ottonwood bears N 3 0" Birch bears N 3 8" Fir bears S 70 ⁰ 1	14,23 and 24, eter, bears N. diameter, bea diameter, bea diameter, bea t was determin nam Creek Road n capped monum 27°W 4.5 fee 7°E 24.5 fee	marked with 81 ^o E. 28 f ars S. 73 ^o E. ars S 80 ^o W., ars N 61 ^o 30' hed that oright d. ment marked t scribed S t scribed S	h 3 notches links dista , 26 links d W., 59 link ginal stone as shown be 14 B.T. and 13 B.T. and	on S. and I m nce, marked T3 distance, marke istance, marke s distance, ma e was destroyed elow from which d posted. d posted.	otch on SINR34WS13B.T ed arked d during	
A 1 A 1	6" Fir bears S 26W ocation poster on a nted monument and a	52.3 feet s a 6" Fir bear	cribed S 23 s S 83 ⁰ E 12	B.T. and po .0 feet.	osted.		

the second second second second second

514 513 523 524 1982 HW 4465	d as shown.					
6" COTTON WOOD BT BIECH BT BT BT	CERTIFICATION Jack H. Ninneman					
SET AN ALUMINUM MONUMENT 3'K 30' MARKED AS SHOWN. N N N N N N N N N N N N N N N N N N	certify the information shown herein is true and correct. Signature Ground Party Chief Jack H. Ninneman I, certify that this Corner Record correctly represents work performed by me or under by direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.) MMM M. Mamman Signature of Surveyor & Seal DateSept.82 Reg. No. 4661S Employer: Ninneman Engineering Inc.					
Office of Clerk and Recorder, County of <u>Lix Collar</u> . This "corner						
record" was filed for record on the $Oct. 20$ day of 19, 82						
was noted on the cross-index plat and is assigned page No. $\frac{1}{1}$	186, in					
book No Eleanorh. Vaughen by County Office	cial deputy					
N-21	31N 34W PMM • - corner this sheet					