INSTRUCTIONS 1. Original and/osequent record used to evaluate the corner position. 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners. 3. Description of monument and accessories set to perpetuate the corner position. 4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc. 5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana. 6. Fill in Cross Index & Section Diagram at bottom of sheet. CERTIFIED CORNER RECORDATION	
I, 1963 record; As per recordation form by J, W, Nimineman "534ES",	Book 1, page 4; filed
II. Found a 1½" iron pipe 5" above ground as shown. From which; A 12" Doug. Fir bears N72°W., 21.6 ft Found a sawed stump at record bearing	. Healed Face.
III, Established S12 BT; A 10" Lodgepole Pine bears N57°E.,	59,3 ft, Mrk,"1/4S12Bt"
Attached location poster to an 8" Do 10,9 ft. Painted red bands around BT's and a	
	, oodo dada bi orgino.
	THOMAS C. HILL 5612 S SURVEY
12"DF 12"DF 12"DF 10"2PPS128 10"2PPS12	I. Susan R. Winslow certify the information shown herein is true and correct. <u>Ausan R. Winslow</u> Signature Ground Party Chief I. Thomas C. Hill
511 512	certify that this Corner Record correctly represents work performed by me or under by direction in compliance with the "Corner Recordation Act" (78-22-101, et seq., M.D.A.)
1963	Signature of Surveyor & Seal Date: <u>12-10-82</u> Reg. No. <u>5612-5</u>
SKETCH OF CORNER	Employer: USES
Office of Clerk and Recorder, County of Lincoln	This "corner Sec. //
record" was filed for record on the $\Delta ec. 29$	day of 19 &
was noted on the cross-index plat and is assigned page No. $\frac{2110}{2110}$, in	
book No <i>Leanor L. Taughu by Betty L. Conces</i> County Official <i>deputy</i> Cross Index No. <u>G-21</u> T. <u>31</u> R. <u>34</u> PMM • Correct this sheet	
Cross Index No. $G = 21$ T. 31 R. 34 PMM • - Corner this sheet	