

CERTIFIED CORNER RECORDATION

INSTRUCTIONS

NORTH & CORNER SECTION 28 T. 32N R. 6E P.M.M. LIBERTY County Corner

AT THE 1 CORNER COMMON TO SECTIONS 21 AND 28, T32N, R6E, P.M.M., LIBERTY COUNTY, MONTANA, WE ESTABLISH THE ORIGINAL POSITION OF THE ORIGINAL STONE AS DESCRIBED IN THE ORIGINAL FIELD NOTES AS FOLLOWS;

SET A GRANITE STONE, 14×10×8 INS. 10 INS IN THE GROUND FOR 40.00 CH 4 SEC. COR., MARKED 4 ON N FACE, DIG PITS, 18x18x12 INS E AND W OF STONE, 3 FT DIST; AND RAISE A MOUND OF EARTH 31 FT BASE 11 FT HIGH N OF COR.

THIS CORNER WAS ESTABLISHED FROM REFERENCES FO THE ORIGINAL MONUMENT PRIOR TO CONSTRUCTION OF THE PAVED STREETS.

WE SET A 5/8" REBAR WITH A $3\frac{1}{2}$ " DOME ALUMINUM CAP AT THE LOCATION OF THE $\frac{1}{2}$ CORNER. WE FIND ADDITIONAL INFORMATION PERTANENT TO THE LOCATION OF THIS CORNER AS SHOWN IN THE SKETCH BELOW.

