510000

INSTRUCTIONS ORIGINAL AND/OR SUBSEQUENT RECORD USED TO EVALUATE THE CORNER POSITION

- 1. DESCRIPTION OF EVIDENCE FOUND, NOTE DISCREPANCIES IN THE RECORD, STATE METHOD OF ESTABLISHING 2. LOST OR OBLITERATED CORNERS.
- DESCRIPTION OF MONUMENT AND ACCESSORIES SET TO PERPETUATE THE CORNER POSITION SKETCH OF CORNER, SHOW ALL PERTINENT DATA THE CORNER POSITION 3.

 - EXAMPLE, CORNER MARKINGS, TOPOGRAPY TIES, POSITION OF ACCESSORIES, ETC.
- CERTIFICATION MUST BE SIGNED AND SEALED BY LAND SURVEYOR REGISTERED IN THE STATE OF MONTANA. 5.
- FILL IN CROSS INDEX, AND SECTION DIAGRAM AT BOTTOM OF SHEET. 6.

CERTIFIED CORNER RECORDATION

CORNER: Northeast, SEC. 5, T. 35 N., R. 48 E., P.M.M., Daniels County, MT

Surveyed by Minott & Gleason in Sept. 1904. **ORIGINAL RECORD:**

Set a sandstone, 15x10x3 ins., 10 ins. in the ground, for cor. of secs. 4, 5, 32 and 33, 80.00 chs. marked with 2 notches on W. and 4 notches on E. edges; dig pits, 18x18x12 ins. in each sec. 51/2 ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

SUBSEQUENT RECORD: None.

4.

EVIDENCE FOUND:

No evidence of original corner. Position of corner falls in county road. A fence bearing north on north side of road.

SET:

Reset the corner using the intersection of the east-west county road and a fenceline extending north. This position fits very well with the found north quarter corner of Section 6 to the west. At the corner point set a std. 30" M.D.T. monument 10" below the road surface with rebar inside. Set M.D.T. witness post to the north at a west-north fence corner. Cap stamped

S 32 | S 33 S4 S 5 7155LS 2000

	*				
N 4 		I, <u>Ji</u> Certi Definition Date	ify the infrombuloff ify the infrombuloff * Signature iff that this Corner formed by me or und "Corner Recordation Signature of Content Signature o	town is true and corre- bf Ground Party Chie Record correctly repre- ter my threefon in con pact d'0-22-101, et s herveyor & Seal Reg. No. <u>7155LS</u>	f sents work
Office of Clerk and Recorder, County of <u>Daniels</u> . This " corner Sec. 5					
record" was fil	led for record on November 21, 2000				
was noted on t	the cross-index plat and is assigned page No			· · · · · · · · · · · · · · · · · · ·	

Cross Index No. A-9, T. 35 N., R. 48 E., PMM

corner this sheet

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors