## 181954

BOOK 146 PAGE 405

## CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVI	DENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)
·	company Nonth & company and Northeast
section corner, Section	corner, North ¼ corner and Northeast 15 from previous survey information
Set North ½ corner Sect survey information	ion 14 from existing pin from previous
Found original stone wi #4 Re-bar and cap.	th $\frac{1}{4}$ chiseled on face of stone and set
DESCRIPTION OF MO	ONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE T	HE ORIGINAL LOCATION OF THIS CORNER: 10/75
See sketch on	reverse side
SKETCH, WITH COURSE AND DISTAN	CE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR I	PASTE REPRODUCTION ON REVERSE SIDE.)
See sketch on re	verse side
ين ايم ا	
51 <sup>3</sup>	
	DIAGRAM OF CORNER:
Surveyor's Seal I, Rodn	ey A. Johnson ne information shown herein is true and N.
correct.	$\int (f_{n}) (f$
Kor	man a Johnson gnature of Ground Party Chief
M	
certify that I	lard Webster have carefully performed or reviewed the
work done on the work d	the diagrammed corner as reported on this rm and approve the same.
	= Corner recorded on the sheet
REGISTERED ST.	Signature of Surveyor
GR - LAN	629 ES
μα <sup>ρ</sup> μα <sup>ρ</sup>	Registration Number
An A Charles I Deviale	State of Montana
ffice of Clerk and Recorder, County of Daniels,	at 3:15 P.M. nd day ofJanuary
ssigned page No. 405-406, in book No. 146	County Official
DRM 125 - 41605 \$ 2.00	Cross Index No. J-13 T. R. VIII MALMATT

