INSTRUCTIONS 1. Original and sequent record used to evaluate the corner position. 2. Description a sence found, note discrepancies in the record, state method of es. ...shing lost or obliterated corners. 3. Description of monument and accessories set to perpetuate the corner position. 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc. 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana. 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner Northeast Section 18 T. 35N R. 54E P.M.M. Sheridan Counly

- 1. 1904 Set a limestone, 24x14x10 ins., 18 ins. in the ground, for Corner of Sections 7, 8, 17 and 18, marked with 4 notches on south and 5 notches on east edge, dig pits 18x18x12 ins. in each section, 5-1/2 ft. distance and raise a mound of earth 2 ft. base, 2 ft. high west of corner.
- 2. 1992 Didn't find a monument at this corner. Found north-south trail and trail going west. Set corner at intersection of trail as best evidence.
- 3. Set 3"x30" M.D.O.T. aluminum monument marked. Set M.D.O.T. steel post 12.7 east.

