6. Fill in Cross Index & Section Diagram at bottom of sheet.						
Corner10	,11,14,15	T. <u></u>	R54E	P.M.M	Sheridan	Count
ecord 1904	Set a limestone, 16X of sections 10, 11, notches on East edge high, west of the cc	14 and 15, market; and raise a mo	ed with 4 na bund of stor	otches on	South and 2	
ound 1991	Limestone rock, 16X8 on the South face ar	X7 inches, 11 in d 2 notches on t	nches in the the East fac	e ground,	with 4 notches	
	At the corner positi in the ground marked of field stones abou	l as shown, at th	K 30" alumir ne center of	num cap ar f the stor	nd post 28 inch ne. Piled a mo	es und
	Buried the stone alc	ngside the monur	ment.			
	Set a 5½ foot steel	reference post i	with MDOH ta	ag, 2 feet	c north of monu	ment.
DEP -	OF MON MENT DO NO, T 35N R54E					
NOT NEN	1991 17 OF HIGH					
 NI					CERTIFICATION	
	L 5 -	' Stl. post W/M	arker	I, Rona	ld T. Arthur nation@newn herein is true an	nd correct.
4	l ,			Konst	Signature Ground Party Chi	326-91
	2			т,В:	ruce Russell	ev.
				by me or under	orner Record correctly represent my direction in compliance (70-22-101, et seq., M.C.A.)	

568 ES of Surveyo Monument CO/STEPE? 568 E PND SURVEIO Date: 2-6-91 Reg. No. MDOH **SKETCH OF CORNER** Employer: Sec. 10 Office of Clerk and Recorder, County of Alexicland _ . This ''corner record" was filed for record on _____ May 8, 1991 was noted on the cross-index plat and is assigned page No. , in book No. _____/55 Eounty Official Depety by Denice 433194 17 Cross Index No. T. 35N R. 54E PMM corner this sheet

(70-22-101, et seq., M.Q.A.)

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors