	INITRUCTIONS 1. Original and basquent record used to evaluate the corner position. 2. Description ance found, note discrepancies in the record, state met corners. 3. Description of monument and accessories set to perpetuate the corner position of monument and accessories set to perpetuate the corner position of accessories, etc.	osition. 1 a skeich example, corner marking,	
	B. Certification must be signed and sealed by Land Surveyor registered in 6. Fill in Cross Index & Section Diagram at boltom of sheet.		
	CERTIFIED CORNER RECO		
Corner	Southeast Section 13 T. 35N R. 541	E P.M.M. Sheridan	County
1.	1904 Set a limestone, 16x14x4 ins., 11 ins. in the ground, for Corner to Sections 13, 18, 19 and 24, marked with 3 notches on south and north edges, dig pits 18x18x12 ins. in each section, 5- 1/2 ft. distance and raise a mound of earth, 4 ft. base, 2 ft. high west of corner.		
2.	1992 Didn't find a monument at this corner. Set corner at fence corner. Fence goes west and south. It fits railroad ties pretty good.		
3.	Set 3"x30" M.D.O.T. aluminum monument marked. Set M.D.O.T. steel post 1° south.		
-			
STA	TE OF MONTAN DO NOTANA		
URVEY MONUT	T35N 13 18 H S		
OFPAR	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$		
	MONUMENT N FENCE + + + + + + + + + + + + + + + + + + +	I. Ri ho d HTHONM certify that a concert to dearted by the second secon	currect.
	× ×	by me or under the direction in completence Recordation Art (1992) Register, at (1, 1) Silenergy, of Suppression A Seat Date: 4/92 Reg. No. 90185	ville the "Corner
	SKETCH OF CORNER	Employer: Interstate Engin	eering, In
Office	of Clerk and Recorder, County of Aleridan "was filed for record on Jenuary 8, 1993	This "corner Sec. 13	
		at 1:00 Pm	+
	oted on the cross-index plat and is assigned page No.	, In	+-+
book N	10. 200 436088 Adapted July 1 2001 Milton E. C D H County Offic Cross Index No. N-25 T.		
	Cruit Index No T.	- Corner	this sheet

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors