CERTIFIED CORNER RECORDATION

Corner	N.E. Sec.	Sec.	36	Т.	36 N	R.	26W-	P.M., MT	Lincoln	Country
	Cor.		•				27W	A 017409 174 A		County

Ι. 1893 G.L.O. Original Record by Peter McCardell et. al.: Set a sandstone, 18x12x8 ins., 12 ins. in the ground, for cor. to secs. 25,30,31&36 mkd. with 1 notch on S. and 5 notches on the N. edges. from which:

A larch, 15 ins. diam., bears N35°E, 22 lks. dist., mkd. "T36N R26W S30 BT".

A larch, 12 ins. diam., bears S73°30E, 34 lks. dist., mkd. "T36N R26W S31 BT".

A larch, 11 ins. diam., bears S69°30W, 54 lks. dist., mkd. "T36N R27W S36 BT".

A pine, 16 ins. diam., bears N38°W, 53 lks. dist., mkd. "T36N R27W S25 BT".

1959-60 B.L.M. Remonumentation Record by David R. Cunningham et. al.: The cor. of secs.25,30,31& 36, monumented with a sandstone, 18x12x8 ins., firmly set, mkd. as described in the original record, and witnessed by the remains of two of the original bearing trees. At the corner point, set an iron post, 30 ins. long, 2 1/2 in. diam., 27 ins. the ground, in concrete, with brass cap mkd. as shown:



Established four new bearing trees:

A larch, 10 ins. diam., bears N77 1/4°E, 21 lks. dist., mkd. "T36N R26W S30 BT".

A fir, 11 ins. diam., bears S42 1/2°E, 89 lks. dist., mkd. "T36N R27W S31 BT". A larch, 13 ins. diam., bears S39°W, 99 lks. dist., mkd. "T36N R27W S36 BT".

A larch, 5 ins. diam., bears N18 1/4°W, 37 lks. dist., mkd. "T36NR27W S25 BT".

Bury the original stone alongside and raise a mound of stone, 3 ft. base, 2 ft. high, W. of the iron post.

Found a 2 1/2 in. diam. iron pipe, firmly set, protruding 7 ins. above the ground, with a 3 1/4 in. diam. II. B.L.M brass cap mkd. as shown above. from which:

A larch, 17 ins. diam., bears N77°E, 13.86 ft. dist., with a healed face. (BLM-record)

A fir, 14 ins. diam., bears S42°E, 58.7 ft. dist., with visible scribe. (BLM-record)

A larch, 17 ins. diam., bears S39°W, 66.0 ft. dist., with a healed face. (BLM-record)

A larch, 9 ins. diam., bears N18°W, 24.4 ft. dist., with a healed face. (BLM-record)

Set a 6 ft. steel post, North, on property line, 3.0 ft. dist. from the corner, with Land Survey Monument III. and Property Boundary decals attached. Painted bearing trees and attached Land Survey Monument and Bearing Tree signs.

ACHTAN

Magnetic Decimation: 20° East.	
Post North 3.0 ft. NTTOE 13.86 ft.	I, <u>Rex O. Rice</u> Certify the information shown herein is true of or get certify the information shown herein is true of or get I. <u>Ronald A. Pearson</u> certify that this Corner Record correctly represents work performed by me of under my direction in compliance with the "Corner Recordation Act" (20-22-101, et seq., M.C.A.) Signature of Surveyor & Seal Date: <u>06/10/97</u>
	Reg. No.: 9008LS
SKETCH OF CORNER	
on was noted on the cross-index plat and in book No CORAL M.CUMMI Coun	sorner record" was filed for record is assigned page No. 983,4 NGS By 2lB ty Official
Cross Index No. V-25 T. 36N	^{R.} 27W ^{Р.М., МТ}

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors