CERTIFIED CORNER RECORDATION

Corner	1/4	Secs.	26 & 27	Т.	36N	R.	28W	P.M., MT	Lincoln	County
--------	-----	-------	---------	----	-----	----	-----	----------	---------	--------

I. <u>1903 G.L.O. Original Record by Gordon B. Smith et. al.</u>: Set a porphyry stone, 12x9x8 ins., 8 ins. in the ground, for 1/4 sec. cor., mkd. "1/4" on W. face.

Established two bearing trees:

A tamarack, 9 ins. diam., bears S83 1/2°E, 30 lks. dist., mkd. "1/4 S26 BT". A fir, 24 ins. diam., bears N29°W, 46 lks. dist., mkd. "1/4 S27 BT".

<u>1970 B.L.M. Remonumentation Record by Joseph E. French</u>: The 1/4 sec. cor. of secs. 26 and 27, monumented with a porphyry stone, 12x9x8 ins., firmly set, mkd. "1/4" on the W. face and witnessed by the remains of the original bearing trees. At the corner point, set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. as shown.



Established two new bearing trees:

A fir, 6 ins. diam., bears S22 1/2°E, 40 lks. dist., mkd. "1/4 S26 BT". A larch, 11 ins. diam., bears N71°W, 33 lks. dist., mkd. "1/4 S27 BT".

Bury the original stone alongside the iron post.

II. Found a 2 1/2 in. diam. iron pipe, protruding 6 ins. above ground, with a 3 1/4 in. diam. B.L.M. brass cap mkd. as shown.

from which:

A fir, 12 ins. diam., bears S22°E, 26.4 ft. dist., with a healed face. (B.L.M. record) A larch, 19 ins. diam., bears S83°E, 19.8 ft. dist., with a healed face. (G.L.O. record) A larch, 14 ins. diam., bears N71°W, 21.8 ft. dist., with a healed face. (B.L.M. record)

III.	Painted bearing trees and attached Land Survey Monu	ment and Bearing Tree signs.
	Magnetic Declination: 20° East	ROWA
	*	I, Thomas M. Hommel
	NZIOW 21.8 G	certify the information shown hereing true end correct
	S83°E 19.8 ft.	I, Ronald A. Pearson
	KS TO BE T	certify that this Corner Record correctly represents work performed by me or under direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C./
	A A A A A A A A A A A A A A A A A A A	Signature of Surveyor & Seal
		Date: <u>3/16/98</u>
	N	Reg. No.: 9008LS

Employer: U.S. FOREST SERVICE

P.M., MT

- corner this sheet

SKETCH OF CORNER

Cross Index No.

	1.0	Se	ec. 26
Office of Clerk and Recorder, County of	TMCOM This "cor	ner record" was filed for	
record on 7-1-98 and was noted or	r the cross-index plat and is as	signed page No. <u>101</u> ,25	
in book No	Carl M. Cum County Off	ming by Del	
	County OI.	lotat	

T-17

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

Τ.

R.

28W

36N