CERTIFIED CORNER RECORDATION

Corner	• N 1/4	Sec.	1	Τ.	36N	R.	28W	P.M., MT	Lincoln	County
I.	1893 G.L.O the ground,	. Original R for the stand	ecord by I dard 1/4 se	Peter Mc ec. cor. m	<u>Cardell</u> kd. "SC	<u>et. al.:</u> 2 1/4 S	Set a po " on N. f	ost, 3 ft. long, ace.	3 ins. square,	24 ins. in
	Established two bearing trees:									
	A pine, 40 ins. diam., bears N06°W, 50 lks. dist., mkd. "SC 1/4 S BT".									
	A pi	ne, 10 ins. c	liam., bear	s S26°30	W, 10	lks. di	st., mkd.	"SC 1/4 S BT	·"'.	
	<u>1977 & 1981 Certified Corner Recordations by D.K. Marquardt Registration No. 2989 ES:</u> No evidence of corner found, set by single proportion, an iron pipe, 36 ins. long, 2 in. diam., 30 ins. in the ground,									
	with brass cap, mkd. as shown:									
				15	3614	R-8W	\ \			
					4 <u>1 S3</u> 4 S1	1 T				
						1977				
					2989 E	es /				
	Established									
	A pir	ne, 8 ins. dia	am., bears	S12°E, 2	9.26 ft.	dist. f	rom the c	corner.		
	A plr	ne, 6 ins. dia	un., bears	мзб~E, 2	10.11 ft.	dist. 1	rom the	corner.		
II.	Found a 2 in. diam. iron pipe, with a 2 in. diam. brass cap, firmly set, protruding 3 ins. above the ground, mkd. as shown above. Cap not mkd. with "CC", as stated in Corner Recordation.									
	from which:									
	A pine, 10 ins. diam., bears S12°E, 29.3 ft. dist., with visible scribe.									
	A pine, 8 ins. diam., bears N36°E, 40.1 ft. dist., with visible scribe.									
III.	Established of									
	A pine, 6 ins. diam., bears East, 1.6 ft. dist., with a Land Survey Monument sign attached.									
	Painted bearing trees and attached Land Survey Monument and Bearing Tree signs. Corner is located South, 12.0 ft. dist. from the centerline of dirt road.									
	Corner 1s loc	ated South,	12.0 ft. di	st. from t	the cent	erline	of dirt ro	ad.	NC	TAN
	Magnetic De	clination: 2	20° East.						PEL	FICN
							ı, <u>Mark</u>	Federman	CERTIFICATION	
			金					certify the informa	10.00	e ante correct.
			2						51)	H / M
		36 10	*				I, <u>Rona</u> certify that direction in	this Corner Resord corr compliance with the "Co	ectly represents work p	performed by me or und
		East	1.6 ft.				1		Act Act	(70-22-101, et seq., M.C
· · · · · ·		S12°E 29.3 EL					Date: 04	Signa 15/97	ture of Surveyor & Seal	
		19.3 ft						9008LS		
			4					U.S. FOREST SEF	VICE	
L	SKETCH OF CORNER					·				
									Se	ec. 1
Office	of Clerk and R	ecorder. Cou	unty of	LINCO	Liv	This "c	orner rec	ord" was filed fo		
on	-							ed page No.		
011		y was wa						ed page No.		
in book	< No		LUI	RAL M.			ty Official	Ky Del	<u> </u>	
						Coun	., ornora			- corner this sheet
		Cros	s Index No.	4-23	т.	361	R.	28W P.M., MT		
		Adopted	July 1, 1981,	Montana Bo	ard of Prof	essional	Engineers	& Land Surveyors		

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors