CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

From: "Subdivisional lines of T9S, R8E". 1883. (1697-453)

"Set granite stone, 12x10x6 ins., 8 ins. in the ground.... marked ‡ on N face, & raised a mound of stone alongside."

Found: An irregular granitic stone of nominal size, lying on the north face (downhill) under a cairn of rock. Marked ‡ on down face.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 7/12/76

Reset rock in original position; cut an "x" in the top; drove a 5/8-in. x 2 ft. rebar alongside the north face for support & magnetic response. Rebuilt mound of stone.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See drawing on reverse of corner record for NW corner of Section 14.

		DIAGRAM OF CORNER:	
Surveyor's Seal	T		
Surveyor a Sour	I,	N.	T9S RSE MPM
	Signature of Ground Party Chief		
	I, Henry A. Rate	1/4	14
	certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.		23
	Signature of Surveyor	= Corner recor	ded on the sheet
	3716S Registration Number		
	142570		
Office of Clerk and Recorder, County	of Park	***************************************	
	ecord on the 27 day of October 19.76, was at 3:30 pm many Cook No. One Cross Index No. 21-19		ss-index plat and is
assigned page No, in	book No. One Court	nty Official	ical
Form 125—3690	Cross Index No. 21 - 19	г. <i>9 &</i> г.	86. Mer.
Tell - 50 cents			