



CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN) From: "Subdivisional lines of T9S, R8E". 1883. (1697-452,453)

"Set a granite stone 14x14x8 in., 9 ins. in the ground....marked 3 notches on S and 2 on E edges and raised a mound of stone alongside."

Found: (On 4/4/76): A granitic stone llx7 in., 7 ins. out of the ground, appropriately marked, firmly set on the south edge of a cairn of travertine rock. A vague "x" had been cut on top. (On 7/12/76): A 4x4x2½ ft. mound of stones had been raised over cairn found earlier. A 5/8-in. rebar had been driven alongside the west face. A fresh "x" had been cut on top.

> DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 7/12/76

None

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See drawing on reverse of corner record for NW corner of Section 14.

		DIAGE	DIAGRAM OF CORNER:	
Surveyor's Seal	I,certify that the information shown herein is true and correct.	n. T9S RSE MPM		
	Signature of Ground Party Chief I, <u>Henry A. Rate</u> certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same. Signature of Surveyor		$\frac{15 14}{22 23}$	
	3716S Registration Number			
Office of Clerk and Recorder, Coun	ty of Park 1.42571 record on the 27 day of October 1976, v	was noted on the	cross-index plat and is	
assigned page No	in book No. Orec. Mar			