INSTRUCTIONS Original and/or subsequent record used to evaluate the corner position. 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners. 3. Description of monument and accessories set to perpetuate the corner position. 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc. 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana. 6. Fill in Cross Index & Section Diagram at bottom of sheet.

**CERTIFIED CORNER RECORDATION** 

Corner <u>1</u> corner, Sections 9 and 10 T. 9 S R. 8 E P.M.M. Park County

1.) Original Record: Set a sandstone,  $16 \times 10 \times 8$  ins., 11 ins. in the ground for  $\frac{1}{4}$  section corner, marked  $\frac{1}{4}$  on West face and raise a mound of stone alongside.

- 2.) Found a sandstone marked as described in the Original Record with mound of stone to West.
- 3.) At the corner position I replaced the found stone with a  $2\frac{1}{2}$ " x 30" aluminum pipe 28" in the ground, with a  $3\frac{1}{4}$ " aluminum cap marked as shown..

From which: A 5/8" rebar with aluminum cap stamped "RM 1" bears S61 W, 21.9 feet. A 5/8" rebar with aluminum cap stamped "RM 2" bears S 23°E, 23.1 feet..

Buried original stone alongside pipe.

95 R8E 1/4 59 \$10

	CERTIFICATION I. Donathon D. Palmer certify the information shows herein is the and correct. <i>Mattian U. Taimur</i> Signature Ground Party Chief I. Mike D. Weldon
SKETCH OF CORNER $181578$	certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" 10-22-101, et seq., M.C.A.)
Office of Clerk and Recorder, County of Park	This ''corner Sec. 9
record" was filed for record on and 15th 1984	@, 11:40 AM
was noted on the cross-index plat and is assigned page No. $79$ , in $-+-+-+-$	
book No Mo Fee Adopted July 1, 1981, Montana Board of Professional Eng	95 R. BE PMM • - corner this sheet